

DM1000 Series

DM1017 - DM1022 - DM1024



Kubota Models	DM1017	DM1022	DM1024
Dimensions and Weight			
Cutting Width (ft)	5'6"	7'2"	7'9"
Weight, approx. (lbs)	860	948	992
Transport Width (ft)	3'9"	3'9"	3'9"
Attachment to Tractor			
Hitch (CAT)	2	2	2
Pin hitch	-	-	-
PTO (RPM)	540	540	540
Minimum PTO horsepower required (hp)	36	42	46
Operation			
Number of disc and knives	4 / 12	6 / 18	6 / 18
Remotes	1	1	1
Cutterbar operating range °	-45 / +45	-45 / +45	-45 / +45
Stubble height (in)	0.78"-1.97"	0.78"-1.97"	0.78"-1.97"
Other Features			
BreakAway	•	•	•
Non-Stop BreakAway	-	-	-
Overrun clutch	•	•	•
Friction clutch	-	-	-
Optional Equipment			
Swath boards (RH)	•	•	•
Swath discs (RH / LH)	o / -	o / -	o / -
High skids (inches) +0.8 / +1.6 / +3.2	• / o / o	• / o / o	• / o / o
Lighting kit	o	o	o
• = standard o = optional - = not available			

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.