

DMC8500

Specifications

DMC8536T - DMC8536R - DMC8540T



Kubota Models	DMC8536T	DMC8536R	DMC8540T
Drawbar	Center	Center	Center
Conditioner	SemiSwing	Roller cond.	SemiSwing
Dimensions and Weight			
Cutting Width (ft)	11'10"	11'10"	13'1"
Weight, approx. (lbs)	5347	5348	5513
Transport Width (ft/m)	11'2"	11'2"	12'6"
Attachment to Tractor			
Hitch (CAT)	Cat II	Cat II	Cat II
PTO (RPM)	540 • / 1000 o	540 • / 1000 o	540 • / 1000 o
Minimum PTO horsepower required (hp/KW)	70/90	70/90	74/100
Operation			
Number of disc	10	10	10
Remotes	2	2	2
Cutterbar operating angle	-15 / +15	-17 / +17	-15 / +15
Stubble height (inch)	1.18"-1.57"	1.18"-1.57"	1.18"-1.57"
Cond. rotor speed	900/600	900	900/600
Tires	380/55-17	380/55-17	380/55-17
Accessories			
Wide spreading kit	o	o	o
High skids (inches) +0.8/+1.6/+3.2	- / • / o	- / • / o	- / • / o
Throwing wings for diff. crops	o	•	o
Lighting kit	•	•	•
Alternative cond. speed kit	1015/500	1200	1015/500
• = standard o = optional - = not available			

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.