

R Series

Specifications

R530



Model				R530	
Type of ROPS / FOPS				CANOPY / CAB	
Engine	Model			V2607-CR-E4	
	Emission certification			Tier4 Final	
	Output (SAE J1995 gross)	HP (kW)/rpm		51.0 (38) / 2400	
	Output (SAE J1349 net)	HP (kW)/rpm		47.9 (35.7) / 2400	
	Displacement	cu.in. (cc)		160 (2615)	
Transmission	Type			Hydrostatic transmission	
Dimensions	Overall length	ft.in. (mm)		17' 4" (5295)	
	Overall height	ft.in. (mm)		8' 1" (2455) / 8' 1" (2475)	
	Overall width (w/o bucket)	ft.in. (mm)		5' 8" (1721)	
	Ground clearance	in. (mm)		12.8" (325)	
Auxiliary circuit	Auxiliary hydraulic flow	gpm (l/min)		14.2 (53.8)	
	Auxiliary hydraulic pressure	psi (Mpa)		2700 (18.6)	
Drive system	Tire size			365/70R18	
	Travel speed	Low / High	mph (km/h)	2.9 (4.6) / 12.4 (20.0)	
	Max. traction force			lbs. (kN)	6540 (29.1)
	Front/Rear axle traction lock				Diff-lock (both axles)
	Articulation angle	deg.		40 (each direction)	
	Angle of rear frame scillation	deg.		±8	
	Loader clearance circle	ft.in. (mm)		25' 4" (7720)	
	Turning radius track circle	ft.in. (mm)		11' 1" (3385)	
	Brakes	Service			Enclosed wet disc
		Parking			Spring applied hydraulic released wet disc
Lifting specifications					
	Tipping load (straight)	with bucket	lbs. (kg)	6041 (2740) / 6537 (2965)	
		with pallet forks	lbs. (kg)	4674 (2120) / 5037 (2285)	
	Tipping load (full turn)	with bucket	lbs. (kg)	5093 (2310) / 5534 (2510)	
		with pallet forks	lbs. (kg)	3968 (1800) / 4288 (1945)	
	Rated operating capacity (SAE)	with bucket	lbs. (kg)	2546 (1155) / 2767 (1255)	
		with pallet forks	lbs. (kg)	1984 (900) / 2144 (972)	
Operational specifications	Standard bucket capacity	yd ³		0.85	
	Breakout force	lbs. (kN)		7761 (34.5)	
	Lifting capacity at ground level	lbs. (kN)		5646 (25.1)	
	Loader raise / lower time	sec.		6.3 / 4.0	
Fuel tank	gal. (l)			18.5 (70)	
Hydraulic system	gal. (l)			14.5 (55)	
Hydraulic reservoir	gal. (l)			10.3 (39)	
Operating weight (Including operator weight @ 175lbs.)				lbs. (kg)	9303 (4220) / 9799 (4445)

Note: The above dimensions are based on the machine with std. tires, skid steer type quick coupler, standard bucket and ROPS/FOPS canopy and cabin. The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective structure (ROPS) and seat belt in almost all applications.