

RA Series

Specifications

RA2072 - RA2076 - RA2584



Kubota Models	RA2072	RA2076	RA2584
FarmLine		•	-
ProLine		-	•
Dimensions and Weight			
Working width (ft)	20'4" - 23'6"	23'/25'7"	24'11"-27'7"
Transport width (ft)	9'2"	9'2"	9'2"
Transport length (ft)		19'4"	20'6"
Parking height (ft)		11'4"*/13'5"	11'4"*/13'5"
Weight (lbs)	3430	3615	4300
Swath width (m)		4'3"-7'3"	4'7"-7'3"
Capacity theo. (acres/h)		20.8	22.7
Hitching system			
Pivoting 3-pt headstock (cat.)		-	-
Lower links (2-pt.)		•	•
Linkage drawbar		-	-
Gauge wheel 16°		-	-
Hitch Type	2Pt	2Pt	2Pt
Other			
Suggested PTO	50	50	50
Carriage Pushed or Pulled	TerraLink	TerraLink	TerraLink
Rotors/Tine arms/Tines			
Rotor diameter (ft)	11'	11'	12'
Swath delivery	center	center	center
Number of rotors	2	2	2
Number of arms per rotor	11	11	2x12
Number of double tines/arm	4	4	4
Tine Arm Style	Curved	Curved	Curved
Removable Tine Arms	•	•	•
Tine diameter (in)		0.35"	0.39"
Continuous cam track		-	•
Detachable tine arms		•	•
Height adjustment		mech.	mech.
Wheels and axles			
Tires (rotors)	16x6.50-8	16x6.50-8	16x6.50-8
Fixed tandem axle	o	o	o
Pivoting tandem axle		-	-
Stand. Tires (carrying frame)		10.0/75-15.3	380/55-17
Optional equipment			
Carrier arm compensating		-	-
Locking catch for slopes		-	-
Safety accessories			
Warning panels		•	•
Road lights	•	•	•

• = standard o = optional - = not available

* = double swath ** = with detached tine arms and lowered headstock

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.