

WR Series

Specifications

WR1100



Kubota Models	WR1100
Weight and Dimensions	
Transport Length (in)	108"
Transport Width (in)	63"
Transport Height (in)	69"
Weight (lbs)	1653
Bale	
Max Bale Size (L x D) (in)	47" x 50"
Max Bale Weight (lbs)	2650
Wrapping Table	
Mounted Wrapper	•
Pull-Type Wrapper	-
Support Rollers/Belts (number)	2/4
Automatic Film Cutter	•
Max. Wrapping Speed (rpm)	30
Pre-stretcher	
1 pre-stretcher 750 mm	•
Pre-Stretcher 29.5" (750mm)	•
Max. wrapping speed (rpm)	30
Operations	
Manual Cable Control (M)	-
Electro Hydraulic Joystick (J)	-
Programmable Computer (C)	•
Remote Control (C)	o
Oil Consumption (l/min)	28
Wheels and Axles	
10.0/80-12	-
Wheels and Axles	
Fill Roll Magazine	-
Adapter Kit for 20" (500mm) Film Spool	o
Bale And Wrap Counter	•
Auto-Stop at End of Wrapping Cycle	•
Film End/Tear Sensor (C)	o
Road Lights	-

• = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.